SVA Industrie Fernseh GmbH

FLOAT BATH ILLUMINANT

Float bath illuminant

Areas of application: waterfence and carbonpusher for optimal illuminating of the monitoring.
Illuminat: halogen 230 VAC, possible up to max. 1000 watt, water and azote cooled.

Specification	
Water supply:	3/4" inner thread
Azote:	Inner thread
up to 2 m:	Diameter 60 mm
ex 2 m:	Diameter 70 mm
Inner width:	92 mm
Length:	up to 4000 mm
Water consumption:	max. 350 l/h
Azote consumption:	max. 250 l/h

Power supply: fixed by terminal box; operation required with isolation transformer.

FLOATBADBELEUCHTUNG

Floatbad Beleuchtung

Einsatzbereiche Waterfence und Carbonpusher zur optimalen Ausleuchtung für die Kamerabeobachtung. Leuchtmittel: Halogen 230 VAC bis max. 1000 Watt möglich. Wasser und Stickstoff gekühlt.

Spezifikationen	
Wasseranschluss:	3/4" Innengewinde
Stickstoff:	Innengewinde
bis 2 m:	ø 60 mm
ab 2 m:	ø 70 mm
Inner width:	92 mm
Länge:	bis 4000 mm
Wasserverbrauch:	max. 350 l/h
Stickstoffverbrauch:	max. 250 l/h

Stromanschluss über Klemmkasten fest. Der Betrieb mit einem Trenntrafo wird empfohlen.

SVA Industrie Fernseh GmbH
Marie-Curie-Straße 11 · 40721 Hilden · Germany · Tel.: +49 (0) 2103 - 33 55 00 · Fax: +49 (0) 2103 - 33 55 01
Internet: www.sva-hilden.de · e-mail: info@sva-hilden.de